

SOB

120V Single Outlet Box with Auto-Resettable Breaker

Transtech’s Single Outlet Box (SOB) series is specially designed for railroad applications. A WAGO connector is provided at the back of unit for fast installation.

SOB2.0 includes a 2A auto-resettable breaker. In case of an overload, the circuit will automatically open without need for fuse replacement or manual reset.

SOB20 et SOB15 have a maximum current rating of 20A or 15A respectively. However, they are not internally current-limited. An appropriate breaker or fuse must be installed in series with these outlets.



SOB2.0-H shown

HIGHLIGHTS

- Single 120V_{AC} outlet
- Surge suppression to protect passenger’s apparatus
- Overload status indicator on the front panel
- Multiple orientation options

SERVICE PROVEN

SOB2.0-H | Stadler US Inc. | Double-deck EMU Caltrain | San Francisco, California, USA

MODELS & FEATURES

Part Number Base	SOB2.0-H	SOB2.0-V	SOB20-H	SOB20-V	SOB15-H	SOB15-V
Operating Voltage	120V _{AC}	120V _{AC}	120V _{AC}	120V _{AC}	120V _{AC}	120V _{AC}
Maximum Output current	2A	2A	20A	20A	15A	15A
Internally Limited Current (Auto-Resettable Breaker Option)	X	X	-	-	-	-
Mount Orientation	Horizontal	Vertical	Horizontal	Vertical	Horizontal	Vertical
Length X Height X Depth 5.55" X 2.28" X 2.22"	X	X	X	X	X	X

X = Included, O = Optional, F = Factory selectable